



ELECTRIC INSTANTANEOUS WATER HEATERS

Electric DHW systems **VITOTHERM EI**



Vitotherm EI

Comfort and mini instantaneous water heaters for fast and efficient provision of hot water

Specification

VITOTHERM EI



Vitotherm EI6



Vitotherm EI4



Vitotherm EI5

		Vitotherm EI6 comfort instantaneous water heater	Vitotherm EI4 comfort instantaneous water heater	Vitotherm EI5 mini instantaneous water heater
Rated output	kW	18/21/24	18/21/24	3.5 or 5.5
Voltage	V	3~/400	400	230
Rated current	A	26/30/35	26/30/35	15.2 or 23.9
Fuse protection	A	32/32/40	32/32/40	16 or 25
Temperature selection	°C	Approx. 30 – 60	Approx. 30 – 60	–
Activation water flow rate	l/min	2.5	2.5	1.2 or 2.0
Mixed water flow rate at 30 K	l/min	8.7 – 11.6	8.7 – 11.6	1,7 or 2,7
Max. inlet temperature	°C	60	60	25
IP rating		IP 25	IP 25	IP 25
Energy efficiency class		< A	< A	< A
Dimensions				
Length (depth)	mm	126	126	76
Width	mm	245	245	168
Height	mm	440	440	200
Special feature		Integral sensors to determine the energy demand	Preferred temperatures can be saved	Instant hot water thanks to bare wire heating system

PRODUCT FEATURES

- + Comfort instantaneous water heaters for quick provision of hot water for various applications
- + Energy saving – only the currently required amount of water is heated
- + Efficient – short pipe runs for fast availability of hot water, saving up to 50 % water and energy
- + Suitable for supplying one or more draw-off points (depending on the appliance type)
- + Mini instantaneous water heaters suitable for oversink and undersink installation

Your trade partner